


GB、DIN GATE VALVE
(WCB, CF8, CF8M, TI, NI)

国标、德标闸阀

国标、德标闸阀
GB、DIN Gate Valve



主要尺寸及重量 Main size and weight

DN(mm)	尺寸 Dimensions (mm)								
	L	D	D1	D2	b-f	z-φd	H	D0	
15	130	95	65	45	12-2	4-φ14	185	120	
20	150	105	75	55	14-2	4-φ14	200	120	
25	160	115	85	65	14-2	4-φ14	225	140	
32	180	135	100	78	16-2	4-φ18	275	160	
40	200	145	110	85	16-3	4-φ18	290	160	
50	250	160	125	100	16-3	4-φ18	345	200	
65	270	180	145	120	18-3	4-φ18	360	220	
80	280	195	160	135	18-3	4-φ18	380	240	
100	300	215	180	155	20-3	8-φ18	430	280	
125	325	245	210	185	22-3	8-φ18	520	300	
150	350	280	240	210	22-3	8-φ23	600	320	
200	400	335	295	265	22-3	8-φ23	765	400	
250	450	390	350	320	24-3	12-φ23	930	450	
300	500	440	400	368	26-3	12-φ23	1080	500	
350	550	500	460	428	26-4	16-φ23	1200	500	
400	600	565	515	482	26-4	16-φ35	1400	550	
450	650	615	656	532	26-4	20-φ25	1500	600	
500	700	670	620	585	28-4	20-φ25	1630	650	
600	800	780	725	685	28-5	20-φ30	1830	700	
700	900	895	840	800	30-5	24-φ30	1930	750	

设计制造标准
Design & Manufacture Standard

设计与制造按GB/T 12234, DIN 3352
结构长度按GB/T 12221, DIN3202
法兰连接尺寸按JB/T 79, DIN 2543
检验按JB/T 9092, DIN 3230

Design and manufacture as GB/T 12234, DIN 3352
Face to face dimensions as GB/T 12221, DIN3202
End flange dimension as JB/T 79, DIN 2543
Pressure test as JB/T 9092, DIN 3230